Europe / Africa Partners Where To Buy



PRODUCT NUMBER: 1011281 Fusion Small (Corded)

Learn more about our products at howardleight.com

Honeywell HOWARD LEIGHT

Overview

Reference Number

1011281

Product Type

Hearing Protection

Range

Earplugs

Line

Reusable Earplugs

Brand

Howard Leight by Honeywell

Industry

- **Product Use**

Multi-Use Earplug

Features & Benefits

Feature

MULTIMATERIAL FUSED DESIGN Combines TPE firm core for easy handling and TPE soft flanges for comfort and fit. QUADRUPLE SOFTFLANGE DESIGN Provides all day comfort and superb attenuation. FLEXIFIRM CORE Easy to grasp, aids in insertion. DETACHABLE CORD SYSTEM Soft braided fabric cord adapts to worker preference or application. HEARPACK STORAGE CASE Easy to stow on a break, store between shifts or keep right at hand. GREEN COLOR Denotes small size.

Benefit

Fusion multiple-use earplugs use advanced manufacturing technology to deliver a revolutionary combination of all-day comfort and easy handling. Its FlexiFirm™ core ensures easy insertion into the ear canal and a superior fit all day long. Fusion's patented SoftFlange™ design adjusts perfectly to the ear canal to deliver unmatched comfort and superior attenuation. Two sizes − regular and small − provide optimal fit for comfort and safety, while its soft braided fabric detachable cord system adapts to any application.

Technical Description

SNR (dB)

28

H (dB)

29

M (dB)

25

L (dB)

24

Attenuation Data

| Frequency (Hz) Frequenz (Hz) Fréquence (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|---|------|------|------|------|------|------|------|------|
| Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB) | 24.6 | 28.3 | 28.6 | 27.9 | 29.4 | 31.0 | 40.0 | 40.9 |
| Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB) | 6.0 | 5.1 | 5.6 | 5.0 | 5.6 | 3.7 | 5.6 | 5.5 |
| Assumed Protection (dB) Angenommener (dB) Protection suppossé (dB) | 18.6 | 23.2 | 23.0 | 22.9 | 23.8 | 27.3 | 34.4 | 35.4 |

Size

Small

Color

Yellow and Green

Shape

flange

Corded

Yes

Weight (grs)

0.68

Certifications

EC Category PPE

2

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0401034

EC Attestation

EC Attestation

EC Attestation Number

200322978 & 200822450

Additional Information

User Manual

Instruction Manual - Fusion

Maintenance

Life Cycle

We recommend replacement every 2-4 weeks.

Storage Information

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

Care Instructions

Our reusable earplugs may be washed in warm water and allowed to air dry. Washing may be repeated several times, but we recommend replacement every 2-4 weeks. Hydrocarbon based solvents, such as alcohol, should not be used to clean reusable ear plugs. The use of such solvent based cleaners may cause reusable plugs to soften, swell, and weaken with time. Additionally, with extended use, reusable plugs must be regularly inspected for serviceability.

Packaging

EAN Code

033552014546

© Honeywell International Inc.