

# TECHNICAL DATA SHEET

**MADDOX BOA® black-grey Low ESD S3S No. 729161**


**Sz. 35 - 48**



## LABELLING ACCORDING TO STANDARD

|   |   |
|---|---|
| Standard for safety footwear<br>EN ISO 20345:2022 S3S | Basic requirement for S3S:<br><b>A</b> Antistatic shoe - <b>E</b> Energy absorption in the heel -<br><b>WPA</b> Water penetration and absorption -<br><b>S</b> Textile penetration protection - Closed heel area - Basic Slip resistance test on ceramic tile + NaLS (soap solution) - Profiled outsole |
| Additional requirements                               | <b>FO FUEL RESISTANCE</b><br><b>SR SLIP RESISTANCE</b> on ceramic tile with glycerine.  |


## FORM







|  |  |
|--|--|
| Safety shoe<br> | Form A - in size 42, the upper height must not exceed 11.2 cm. |
|--|--|

## AREAS OF APPLICATION

|                      |   |
|----------------------|---|
| Areas of application | Indoors and outdoors<br>Areas where exposure to moisture is expected (S2)<br>Areas where there is a risk of penetration from pointed and sharp objects (S3/S3L/S3S)<br><br>Areas where there is a risk of electrostatic discharge (ESDS/ESD)<br><br>Workplaces on hard Undergrounds: The revolutionary Infinergy® sole core cushions impacts and provides for a rebound effect when the compressive impulse subsides - for more energy in every step. |
|----------------------|---|

## FEATURES

|                      |  |   |
|----------------------|--|---|
| ESD equipment        | Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1. |  |
| Sizes (unisex model) | <ul style="list-style-type: none"> <li>Expanded size range: available in sizes 35 - 48</li> </ul>  |   |

| FEATURES  |  |   |
|---|--|---|
| Certification in accordance with DGUV rule 112-191  | <ul style="list-style-type: none"> <li>• Certified for orthopaedic modifications / inserts</li> </ul>  |    |
| Padded upper edge   | <ul style="list-style-type: none"> <li>• Excellent wearing comfort: the padded upper edge protects the Achilles tendon.</li> </ul>   |   |
| Padded tongue   | <ul style="list-style-type: none"> <li>• Excellent wearing comfort: The tongue prevents pressure marks.</li> </ul>   |   |
| Reflective material   | <ul style="list-style-type: none"> <li>• Good visibility in the dark</li> </ul>  |    |
| Heel loop   | <ul style="list-style-type: none"> <li>• Quicker into the shoe: The heel loop makes it easier to get inside the shoe</li> </ul>  |   |
| Sole core made of Infinergy® by BASF<br> | The sole core consists of expanded, thermoplastic polyurethane in the form of oval foam beads. These stick together and are very light and elastic. This revolutionary technology cushions the impact and bounces back extremely well on pressure, so that the energy can be returned to the wearer. Even under low temperatures of -20 °C, the core maintains its high elasticity.  |    |
| BOA® Fit System   | Delivering fit solutions purpose-built for performance, the BOA® Fit System is featured in products across industries (including sports, workwear and medical) and consists of three integral parts: a micro adjustable dial, a super-strong lightweight lace and low friction lace guides. Each unique configuration is engineered for fast, effortless, precision fit and is backed by the BOA® Guarantee.   |    |
| Leather-free equipment  | <ul style="list-style-type: none"> <li>• Suitable for persons allergic to leather</li> </ul>   |   |
| Ergonomic Product IGR certification   | The IGR quality seal (Interessengemeinschaft der Rückenschullehrer/-innen e.V. / Association of back specialists) confirms the highly praised features and practical functionality of the tested products. The IGR certification attests the degree of the product's customisability to the physical characteristics of the test person. In accordance with DIN 33419 / EN ISO 15537, the product's usability and ergonomics were tested. Products recommended by IGR e.V. bear the title "Ergonomic Product". |  |
| UPPER MATERIAL  |  |   |
| Hydrophobized microfibre  | <ul style="list-style-type: none"> <li>• Areas of application S2/S3</li> <li>• Synthetic material</li> <li>• Particularly soft</li> <li>• Retains its shape</li> <li>• Tear-resistant</li> <li>• Dries quickly</li> <li>• Abrasion-resistant and light</li> <li>• Water penetration and absorption in accordance with EN ISO 20345 S2; an improved resistance against water penetration is achieved by a special hydrophobation of the material</li> </ul>   |   |

## UPPER MATERIAL

Hydrophobized textile material

- Areas of application S2/S3
- Synthetic material
- Shape-retaining
- Tear-resistant
- Dries quickly
- Wear-resistant and light
- Water penetration/absorption in accordance with EN ISO 20345 S2
- By hydrophobation, higher resistance against water penetration and water absorption

## LINING

Breathable fabric lining

- Climate-regulating
- Good ventilation
- Skin-friendly
- High absorption and emission of moisture

Heel pocket lining

- The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.

## TOE PROTECTION CAP

Steel toe cap



- Protection against impacts of min. 200 joules and pressure loading of min. 15 kN
- Permanent edge coverage for cushioning
- Ergonomically shaped
- Comfortable toe room
- Good coverage of the little toe area

## INLAY SOLE

Full-length inlay sole  
SPORTIVE ESD



- ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.

## PENETRATION RESISTANCE

Metal-free penetration protection

The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees.

The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.

## OUTSOLE

MAXXIMO extended wedge double-density sole



- Excellent slip resistance
- Antistatic

Outsole: TPU (thermoplastic polyurethane)

- Colour: black
- Profile depth: 3.5 mm
- Particularly abrasion-resistant
- Heat-resistant to approx. 130°C
- Flexible at cold temperatures to approx. -30°C
- Oil and fuel resistant

Midsole: PU (polyurethane) with a core made of Infinergy® by BASF

- The soft PU core provides a good impact absorption and high wearing comfort
- The core made of Infinergy® provides a very good cushioning with rebound effect