



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	33-3054-5	Version number:	15.00
Revision date:	26/11/2025	Supersedes date:	11/09/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Neoprene High Performance Rubber and Gasket Adhesive 1300L

Product Identification Numbers

UU-0015-1018-7 UU-0015-1694-5

7100036384 7100036550

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Product

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225
 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms

Ingredient	CAS Nbr	EC No.	% by Wt
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		927-510-4	< 25
butanone	78-93-3	201-159-0	10 - 25

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapours.
P273	Avoid release to the environment.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.
P391	Collect spillage.

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH208

Contains rosin. May produce an allergic reaction.

Contains 16% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	(EC-No.) 927-510-4	< 25	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex	(CAS-No.) 68037-42-3	10 - 20	Substance not classified as hazardous
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	(EC-No.) 931-254-9	< 20	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336
Polychloroprene	(CAS-No.) 9010-98-4	7 - 13	Substance not classified as hazardous
propyl acetate	(CAS-No.) 109-60-4 (EC-No.) 203-686-1	7 - 13	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 Nota C
zinc oxide	(CAS-No.) 1314-13-2 (EC-No.) 215-222-5	< 1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
rosin	(CAS-No.) 8050-09-7 (EC-No.) 232-475-7	< 1	Skin Sens. 1B, H317
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	(CAS-No.) 68610-51-5 (EC-No.) 271-867-2	< 0.5	Aquatic Chronic 4, H413 Repr. 2, H361d
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	< 0.25	Substance with a national occupational exposure limit

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons.
Carbon monoxide
Carbon dioxide.
Hydrogen Chloride

Condition

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
propyl acetate	109-60-4	UK HSE	TWA:849 mg/m ³ (200 ppm);STEL:1060 mg/m ³ (250 ppm)	
Dust, inhalable dust	1314-13-2	UK HSE	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	
Talc	14807-96-6	UK HSE	TWA(as respirable dust):1 mg/m ³	
butanone	78-93-3	UK HSE	TWA: 600 mg/m ³ (200 ppm); STEL: 899 mg/m ³ (300 ppm)	SKIN
rosin	8050-09-7	UK HSE	TWA(as fume):0.05 mg/m ³ ;STEL(as fume):0.15 mg/m ³	Respiratory Sensitizer

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
butanone	78-93-3	UK EH40 BMGVs	Butan-2-one	Urine	EOS	70 umol/L	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polyvinyl alcohol (PVA).	>.3	=>8 hours
Polymer laminate	>.3	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Yellow
Odor	Light Solvent
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=48 °C [Details:Data for Aliphatic hydrocarbons]
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	<=0 °C [Test Method:Closed Cup] [Details:Data for Aliphatic hydrocarbons]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	353 mm ² /sec
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	No data available.
Relative density	0.85 - 0.87 [Ref Std:WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	67.5 - 74.5 %
Evaporation rate	No data available.
Percent volatile	67.5 - 74.5 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the

cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Peripheral neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
butanone	Inhalation-Vapour (4 hours)	Rat	LC50 34.5 mg/l
butanone	Ingestion	Rat	LD50 2,737 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 2,920 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation-Vapour (4 hours)	Rat	LC50 > 14.7 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation-Vapour (4 hours)	Rat	LC50 > 23.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation-Vapour (4 hours)	Rat	LC50 > 5.61 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,840 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Dermal	Rabbit	LD50 > 2,920 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Inhalation-Vapour (4	Rat	LC50 > 14.7 mg/l

	hours)		
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 23.3 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 5.61 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Ingestion	Rat	LD50 > 5,840 mg/kg
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Ingestion	Rat	LD50 > 5,000 mg/kg
Polychloroprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
propyl acetate	Dermal	Rabbit	LD50 > 17,756 mg/kg
propyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 16.7, < 33.4 mg/l
propyl acetate	Ingestion	Rat	LD50 > 8,700 mg/kg
zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg
rosin	Ingestion	Rat	LD50 > 7,600 mg/kg
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Dermal	Rat	LD50 > 2,000 mg/kg
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Ingestion	Rat	LD50 > 5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
butanone	Rabbit	Minimal irritation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	Irritant
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Rabbit	Irritant
Polychloroprene	Human	No significant irritation
propyl acetate	Rabbit	No significant irritation
zinc oxide	Human and animal	No significant irritation
rosin	Rabbit	No significant irritation
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
butanone	Rabbit	Severe irritant
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	No significant irritation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	Mild irritant
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Rabbit	No significant irritation
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Rabbit	Mild irritant
Polychloroprene	Professional judgement	No significant irritation
propyl acetate	Rabbit	Moderate irritant
zinc oxide	Rabbit	Mild irritant

rosin	Rabbit	Mild irritant
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Guinea pig	Not classified
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Guinea pig	Not classified
propyl acetate	similar compounds	Not classified
zinc oxide	Guinea pig	Not classified
rosin	Guinea pig	Sensitising
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
rosin	Human	Not classified
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
butanone	In Vitro	Not mutagenic
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	In Vitro	Not mutagenic
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	In Vitro	Not mutagenic
propyl acetate	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	In Vitro	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
butanone	Inhalation	Human	Not carcinogenic
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Talc	Dermal	Human	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8	during

				mg/l	gestation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
propyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
butanone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Neoprene High Performance Rubber and Gasket Adhesive 1300L

Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
propyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Cat	NOAEL NA	
propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
propyl acetate	Inhalation	nervous system	Not classified	Rat	NOAEL NA	4 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
butanone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
propyl acetate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.6 mg/l	90 days
propyl acetate	Inhalation	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder vascular system	Not classified	Rat	NOAEL 6.4 mg/l	90 days
zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	Ingestion	endocrine system blood liver eyes	Not classified	Rat	NOAEL 289 mg/kg/day	90 days
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks

Aspiration Hazard

Name	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Aspiration hazard
Hydrocarbons, C6, isoalkanes, < 5% n- hexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Analogous Compound	72 hours	EL50	29 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Medaka	Analogous Compound	96 hours	LC50	0.561 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Analogous Compound	48 hours	EC50	0.4 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Fathead minnow	Estimated	96 hours	LL50	8.2 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	EL50	3.1 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	EL50	29 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	EL50	55 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	48 hours	EL50	3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	48 hours	LC50	3.9 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Rainbow trout	Experimental	96 hours	LL50	>13.4 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Analogous Compound	72 hours	NOEL	6.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Analogous Compound	21 days	NOEC	0.17 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	NOEL	0.5 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	NOEL	6.3 mg/l

isoalkanes, cyclics						
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	NOEL	30 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	21 days	NOEL	1 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	21 days	NOEL	2.6 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Activated sludge	Analogous Compound	15 hours	IC50	29 mg/l
butanone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex	68037-42-3	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Analogous Compound	72 hours	EL50	29 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Medaka	Analogous Compound	96 hours	LC50	0.561 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Analogous Compound	48 hours	EC50	0.4 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Fathead minnow	Estimated	96 hours	LL50	8.2 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Estimated	72 hours	EL50	3.1 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Estimated	72 hours	EL50	29 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Estimated	72 hours	EL50	55 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Estimated	48 hours	EL50	3 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Estimated	48 hours	LC50	3.9 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Rainbow trout	Experimental	96 hours	LL50	>13.4 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Analogous Compound	72 hours	NOEL	6.3 mg/l

Neoprene High Performance Rubber and Gasket Adhesive 1300L

Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Analogous Compound	21 days	NOEC	0.17 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Estimated	72 hours	NOEL	0.5 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Estimated	72 hours	NOEL	6.3 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Green algae	Estimated	72 hours	NOEL	30 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Estimated	21 days	NOEL	1 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Water flea	Estimated	21 days	NOEL	2.6 mg/l
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Activated sludge	Analogous Compound	15 hours	IC50	29 mg/l
propyl acetate	109-60-4	Activated sludge	Experimental	16 hours	IC50	>1,000 mg/l
propyl acetate	109-60-4	Fathead minnow	Experimental	96 hours	LC50	56 mg/l
propyl acetate	109-60-4	Green algae	Experimental	72 hours	EC50	672 mg/l
propyl acetate	109-60-4	Water flea	Experimental	48 hours	EC50	91.5 mg/l
propyl acetate	109-60-4	Green algae	Experimental	72 hours	NOEC	83.2 mg/l
Polychloroprene	9010-98-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
rosin	8050-09-7	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
rosin	8050-09-7	Zebra Fish	Experimental	96 hours	LL50	>1 mg/l
rosin	8050-09-7	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
rosin	8050-09-7	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
rosin	8050-09-7	Bacteria	Experimental	N/A	EC50	76.1 mg/l
zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Bacteria	Experimental	17 hours	NOEC	150.9 mg/l
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA	68610-51-5	Green algae	Experimental	72 hours	EC50	>100 mg/l

DIENE AND ISOBUTYLENE						
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Water flea	Experimental	48 hours	EC50	>100 mg/l
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Fathead minnow	Experimental	34 days	NOEL	100 mg/l
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Green algae	Experimental	72 hours	NOEC	100 mg/l
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Water flea	Experimental	21 days	EC10	<1 mg/l
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Analogous Compound Biodegradation	28 days	BOD	74.4 %BOD/ThOD	OECD 301F - Manometric respirometry
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Biodegradation	28 days	BOD	77 %BOD/ThOD	OECD 301F - Manometric respirometry
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Biodegradation	28 days	BOD	98 %BOD/COD	OECD 301F - Manometric respirometry
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Biodegradation	28 days	BOD	98 %BOD/COD	OECD 301F - Manometric respirometry
butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301D - Closed bottle test
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex	68037-42-3	Data not available or insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Analogous Compound Biodegradation	28 days	BOD	74.4 %BOD/ThOD	OECD 301F - Manometric respirometry

Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Estimated Biodegradation	28 days	BOD	77 %BOD/ThOD	OECD 301F - Manometric respirometry
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Estimated Biodegradation	28 days	BOD	98 %BOD/COD	OECD 301F - Manometric respirometry
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Estimated Biodegradation	28 days	BOD	98 %BOD/COD	OECD 301F - Manometric respirometry
propyl acetate	109-60-4	Experimental Biodegradation	14 days	BOD	81 %BOD/ThOD	OECD 301C - MITI test (I)
Polychloroprene	9010-98-4	Data not available or insufficient	N/A	N/A	N/A	N/A
rosin	8050-09-7	Experimental Biodegradation	28 days	CO2 evolution	89 %CO2 evolution/THCO2 evolution	OECD 301B - Modified Sturm or CO2
zinc oxide	1314-13-2	Data not available or insufficient	N/A	N/A	N/A	N/A
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTADIENE AND ISOBUTYLENE	68610-51-5	Experimental Biodegradation	28 days	CO2 evolution	1 % weight	OECD 301B - Modified Sturm or CO2
Talc	14807-96-6	Data not available or insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	540	OECD305-Bioconcentration
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Bioconcentration		Log Kow	3.6	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Analogous Compound Bioconcentration		Log Kow	4.66	
butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.3	OECD 117 log Kow HPLC method
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex	68037-42-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	540	OECD305-Bioconcentration
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Estimated Bioconcentration		Log Kow	3.6	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Analogous Compound Bioconcentration		Log Kow	4.66	
propyl acetate	109-60-4	Experimental Bioconcentration		Log Kow	1.4	
Polychloroprene	9010-98-4	Data not available or insufficient for	N/A	N/A	N/A	N/A

		classification				
rosin	8050-09-7	Analogous Compound BCF - Fish	20 days	Bioaccumulation factor	≤129	
rosin	8050-09-7	Experimental Bioconcentration		Log Kow	6.2	OECD 117 log Kow HPLC method
zinc oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	≤217	OECD305-Bioconcentration
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Modeled Bioconcentration		Bioaccumulation factor	≤55	Catalogic™
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Modeled Mobility in Soil	Koc	≥202 l/kg	Episuite™
Hydrocarbons, C6, isoalkanes, < 5% n-hexane	931-254-9	Modeled Mobility in Soil	Koc	≥202 l/kg	Episuite™
rosin	8050-09-7	Modeled Mobility in Soil	Koc	124 l/kg	ACD/Labs ChemSketch™
P-CRESOL, REACTION PRODUCTS WITH DICYCLOPENTA DIENE AND ISOBUTYLENE	68610-51-5	Experimental Mobility in Soil	Koc	>427000 l/kg	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09*

Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN1133	UN1133	UN1133
14.2 UN proper shipping name	ADHESIVES	ADHESIVES	ADHESIVES (ZINC OXIDE)
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	II	II	II
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient****CAS Nbr****Classification****Regulation**

Polychloroprene

9010-98-4

Gr. 3: Not classifiable

International Agency
for Research on Cancer

Talc

14807-96-6

Grp. 2A: Probable
human carc.International Agency
for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500
P5c FLAMMABLE LIQUIDS*	5000	50000

*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information**List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Revision information:

GB Section 15: Carcinogenicity information information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 8: glove data value information was added.

Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 8: Respiratory protection - recommended respirators information information was modified.

Section 9: Specific physical form information information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Cancer Hazards information information was added.

Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Respiratory Sensitization Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.