

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Pro Foam C&F  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use, Professional use  
Use of the substance/mixture : Polyurethane

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Rectavit N.V. N.V.  
Ambachtenlaan 4  
9080 Lochristi  
Belgium  
T +32 9 216 85 20 - F +32 9 216 85 30  
[msds@rectavit.be](mailto:msds@rectavit.be) - [www.Rectavit.be](http://www.Rectavit.be)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Acute toxicity (inhalation:dust,mist) Category 4 H332  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Respiratory sensitisation, Category 1 H334  
Skin sensitisation, Category 1 H317  
Carcinogenicity, Category 2 H351  
Reproductive toxicity, Additional category, Effects on or via lactation H362  
Specific target organ toxicity – Single exposure, Category 3, H335  
Respiratory tract irritation  
Specific target organ toxicity – Repeated exposure, Category 2 H373

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment – Chronic Hazard, H413  
Category 4

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause harm to breast-fed children. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause long lasting harmful effects to aquatic life.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

Extra phrases

- : Danger
- : polymethylene polyphenyl isocyanate; alkanes, C14-17, chloro
- : H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 - May cause respiratory irritation.  
H351 - Suspected of causing cancer.  
H362 - May cause harm to breast-fed children.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H413 - May cause long lasting harmful effects to aquatic life.
- : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- : Persons already sensitised to diisocyanates may develop allergic reactions when using this product.  
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.  
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.  
As from 24 August 2023 adequate training is required before industrial or professional use.

## 2.3. Other hazards

Contains PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

### Component

dimethyl ether (115-10-6)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII  
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component	
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
isobutane (75-28-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
polymethylene polyphenyl isocyanate (9016-87-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
alkanes, C14-17, chloro (85535-85-9)	This substance meets the PBT criteria of REACH regulation, annex XIII This substance meets the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
alkanes, C14-17, chloro(85535-85-9)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
polymethylene polyphenyl isocyanate	CAS-No.: 9016-87-9	≥ 25 – < 50	Carc. 2, H351 Resp. Sens. 1, H334 Skin Sens. 1, H317 Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) STOT RE 2, H373 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
alkanes, C14-17, chloro substance listed as REACH Candidate (Medium-chain chlorinated paraffins (MCCP)) PBT substance; vPvB substance	CAS-No.: 85535-85-9 EC-No.: 287-477-0 EC Index-No.: 602-095-00-X REACH-no: 01-2119519269-33	≥ 10 – < 25	Lact., H362 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10) EUH066
dimethyl ether (Propellant gas) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	≥ 10 – < 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
isobutane (Propellant gas)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane (Propellant gas)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	≥ 1 – < 5	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
reaction products of phosphoryl trichloride and 2-methyloxirane	CAS-No.: 1244733-77-4 EC-No.: 807-935-0 REACH-no: 01-2119486772-26	≥ 1 – < 5	Acute Tox. 4 (Oral), H302 (ATE=632 mg/kg bodyweight) Aquatic Chronic 3, H412

Comments : polymethylene polyphenyl isocyanate, contains > 0.1% MDI isomers  
Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.  
Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Explosion risk in case of fire. Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours, spray, mist. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Leave the product to solidify. Mechanically recover the product. Carefully collect the spill/leftovers. Take collected spill to manufacturer/competent authority. Notify authorities if product enters sewers or public waters. Wash clothing and equipment after handling.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact during pregnancy/while nursing. Do not breathe vapours, spray, mist. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible products : Heat sources. Ignition sources. Strong bases. Strong acids.

Packaging materials : Aerosol.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

###### dimethyl ether (115-10-6)

###### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Dimethylether
------------	---------------

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>dimethyl ether (115-10-6)</b>	
IOEL TWA	1920 mg/m <sup>3</sup>
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Oxyde de diméthyle # Dimethylether
OEL TWA	1920 mg/m <sup>3</sup>
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>propane (74-98-6)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>isobutane (75-28-5)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan
OEL STEL	2370 mg/m <sup>3</sup>
OEL STEL [ppm]	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>dimethyl ether (115-10-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, inhalation	1894 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, inhalation	471 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,155 mg/l
PNEC aqua (marine water)	0,016 mg/l
PNEC aqua (intermittent, freshwater)	1,549 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0,681 mg/kg dwt
PNEC sediment (marine water)	0,069 mg/kg dwt

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>dimethyl ether (115-10-6)</b>	
<b>PNEC (Soil)</b>	
PNEC soil	0,045 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	160 mg/l
<b>reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	22,6 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	2,91 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	8,2 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	5,6 mg/m <sup>3</sup>
Acute - systemic effects, oral	2 mg/kg bodyweight
Long-term - systemic effects, oral	0,52 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,45 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1,04 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,32 mg/l
PNEC aqua (marine water)	0,032 mg/l
PNEC aqua (intermittent, freshwater)	0,51 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	11,5 mg/kg dwt
PNEC sediment (marine water)	1,15 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,34 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	11,6 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	19,1 mg/l
<b>alkanes, C14-17, chloro (85535-85-9)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	47,9 mg/kg bw/day
Long-term - systemic effects, inhalation	6,7 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0,58 mg/kg bw/day
Long-term - systemic effects, inhalation	2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	28,75 mg/kg bw/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	1 µg/l

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

alkanes, C14-17, chloro (85535-85-9)	
PNEC aqua (marine water)	0,2 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	13 mg/kg dwt
PNEC sediment (marine water)	2,6 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	11,9 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	10 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	80 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses (EN 166)

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Protective clothing (EN 14605 or EN 13034)

##### Hand protection:

Protective gloves against chemicals (EN 374)

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: milky. Grey. orange.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: In the pressurized container the vapour pressure exceeds 500 kPa. After foam release, the vapour pressure is very low (not declared)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 23 %

##### 9.2.2. Other safety characteristics

VOC content : 23,41 – 24,06 % (222.35 g/l - 228.57 g/l)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Polymerisation risk. Reacts with (some) acids/bases.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Harmful if inhaled.

Pro Foam C&F	
ATE CLP (dust,mist)	4,852 mg/l/4h
dimethyl ether (115-10-6)	
LC50 Inhalation - Rat [ppm]	164000 ppm (4 h, Rat, Male, Experimental value, Inhalation (gases), 14 day(s))
propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
polymethylene polyphenyl isocyanate (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)	
LD50 oral rat	632 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 7 mg/l/4h
alkanes, C14-17, chloro (85535-85-9)	
LD50 oral rat	> 4000 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 13500 mg/kg bodyweight (24 h, Rabbit, Read-across, Dermal)
LC50 Inhalation - Rat	> 48,17 mg/l air (1 h, Rat, Read-across, Inhalation (vapours))
Skin corrosion/irritation	: Causes skin irritation.
propane (74-98-6)	
pH	No data available in the literature
polymethylene polyphenyl isocyanate (9016-87-9)	
pH	No data available in the literature
Serious eye damage/irritation	: Causes serious eye irritation.
propane (74-98-6)	
pH	No data available in the literature
polymethylene polyphenyl isocyanate (9016-87-9)	
pH	No data available in the literature
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
polymethylene polyphenyl isocyanate (9016-87-9)	
IARC group	3 - Not classifiable

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reproductive toxicity : May cause harm to breast-fed children.  
STOT-single exposure : May cause respiratory irritation.

### polymethylene polyphenyl isocyanate (9016-87-9)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

### polymethylene polyphenyl isocyanate (9016-87-9)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure (if inhaled).

Aspiration hazard : Not classified

### Pro Foam C&F

Vaporizer : Aerosol

### propane (74-98-6)

Viscosity, kinematic : No data available in the literature

### isobutane (75-28-5)

Viscosity, kinematic : 0,013 mm<sup>2</sup>/s

### polymethylene polyphenyl isocyanate (9016-87-9)

Viscosity, kinematic : No data available in the literature

### alkanes, C14-17, chloro (85535-85-9)

Viscosity, kinematic : 90 – 12000 mm<sup>2</sup>/s (20 °C)

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.  
Hazardous to the aquatic environment, short-term (acute) : Not classified.  
Hazardous to the aquatic environment, long-term (chronic) : May cause long lasting harmful effects to aquatic life.  
Not rapidly degradable

### dimethyl ether (115-10-6)

LC50 - Fish [1] : > 4100 mg/l (NEN 6504: Water - Determination of toxicity with *Poecilia reticulata*, 96 h, *Poecilia reticulata*, Semi-static system, Fresh water, Experimental value, Lethal)

EC50 - Crustacea [1] : > 4400 mg/l (NEN 6501: Water - Determination of toxicity with *Daphnia magna*, 48 h, *Daphnia magna*, Static system, Fresh water, Experimental value, Lethal)

EC50 96h - Algae [1] : 154,9 mg/l (ECOSAR v1.00, Algae, QSAR, Estimated value)

### propane (74-98-6)

LC50 - Fish [1] : 49,9 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)

EC50 96h - Algae [1] : 11,89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

### isobutane (75-28-5)

LC50 - Fish [1] : 27,98 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)

EC50 96h - Algae [1] : 8,57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)
<b>reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)</b>	
LC50 - Fish [1]	51 mg/l Pimephalis promelas
EC50 - Crustacea [1]	131 mg/l Daphnia magna
EC50 72h - Algae [1]	82 mg/l Pseudokirchnerella subcapitata
NOEC chronic crustacea	32 mg/l
NOEC chronic algae	13 mg/l
<b>alkanes, C14-17, chloro (85535-85-9)</b>	
LC50 - Fish [1]	> 5000 mg/l (Equivalent or similar to OECD 203, 96 h, Alburnus alburnus, Static system, Brackish water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	0,006 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 3,2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
<b>12.2. Persistence and degradability</b>	
<b>dimethyl ether (115-10-6)</b>	
Persistence and degradability	not readily degradable in water.
<b>propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>isobutane (75-28-5)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
Persistence and degradability	not readily degradable in water.
<b>reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)</b>	
Persistence and degradability	not readily degradable in water.
Biodegradation	14 % OECD 301E
<b>alkanes, C14-17, chloro (85535-85-9)</b>	
Persistence and degradability	not readily degradable in water.
<b>12.3. Bioaccumulative potential</b>	
<b>dimethyl ether (115-10-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	0,1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>propane (74-98-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>isobutane (75-28-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
BCF - Fish [1]	268,1 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	10,46 (Calculated, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)</b>	
BCF - Fish [1]	0,8 – 14
Partition coefficient n-octanol/water (Log Pow)	2,68
<b>alkanes, C14-17, chloro (85535-85-9)</b>	
BCF - Fish [1]	6660 – 9140 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 35 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4,7 – 8,3 (Experimental value, Equivalent or similar to OECD 117)
Bioaccumulative potential	highly bioaccumulative.

### 12.4. Mobility in soil

<b>propane (74-98-6)</b>	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).
<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9,078 – 10,597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Product adsorbs onto the soil.
<b>reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2,24
<b>alkanes, C14-17, chloro (85535-85-9)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5 – 5,2 (log Koc, Experimental value)
Ecology - soil	Low potential for mobility in soil.

### 12.5. Results of PBT and vPvB assessment

<b>Component</b>	
dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
isobutane (75-28-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component	
polymethylene polyphenyl isocyanate (9016-87-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
alkanes, C14-17, chloro (85535-85-9)	This substance meets the PBT criteria of REACH regulation, annex XIII This substance meets the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: This material and its container must be disposed of as hazardous waste.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 05 01* - waste isocyanates 16 05 04* - gases in pressure containers (including halons) containing dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

#### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Pro Foam C&F	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Pro Foam C&F ; polymethylene polyphenyl isocyanate ; reaction products of phosphoryl trichloride and 2-methyloxirane ; alkanes, C14-17, chloro	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Pro Foam C&F ; reaction products of phosphoryl trichloride and 2-methyloxirane ; alkanes, C14-17, chloro	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
56.	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI)
56(a)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate
56(b)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,4'-Methylenediphenyl diisocyanate
56(c)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,2'-Methylenediphenyl diisocyanate
74.	polymethylene polyphenyl isocyanate	Diisocyanates, O = C=N-R-N = C=O, with R an aliphatic or aromatic hydrocarbon unit of unspecified length

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations  $\geq 0.1\%$  or SCL: alkanes, C14-17, chloro (EC 287-477-0, CAS 85535-85-9)

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content : 23,41 – 24,06 % (222.35 g/l - 228.57 g/l)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes

Section	Changed item	Change	Comments
	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878		

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.

# Pro Foam C&F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
Lact.	H362	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 4	H413	Expert judgement

Safety Data Sheet (SDS), EU-2023-1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.