

TECHNICAL SPECIFICATION

EYE PROTECTION



EVOGuard™ C5-MAX

EVOGuard™ C5-MAX / Code: ADA280-070-000



FEATURES



Compatibility

EVOGuard™ visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Impact

Five high performance visors offering up to A rated impact resistance when fitted to a safety helmet and fully compatible with EVOGuard™ browguard for medium energy impact protection.



Coverage

EVOGuard™ visors provide comprehensive facial coverage without limiting movement. EVOGuard™ MAX visors offer enhanced coverage with an integral chinguard.

SAFETY STANDARDS

EN 166 EN 170 GS-ET-29

SPECIFICATIONS



ULTRAVIOLET FILTER SCALE NUMBER
2C-1.2



MANUFACTURERS TRADEMARK
JSP Dagger



OPTICAL QUALITY (1=HIGH, 3=LOW)
1



HIGH ENERGY IMPACT 190 M/S
A - When Fitted To EVO Helmets



MEDIUM ENERGY IMPACT 120 M/S
B - When Fitted To EVOGuard Browguard



FOR PROTECTION AT EXTREMES OF TEMPERATURE
T



RESISTANCE TO LIQUID SPLASH
3



RESISTANCE TO SHORT CIRCUIT ELECTRIC ARC
8 GS/ET/29

ARC FLASH PROTECTION CLASS

1: Up To 4kA, or 155kJ/m² or 3.7cal/cm²

VISIBLE LIGHT TRANSMITTANCE (VLT)

0, superior or equal to 75%



RESISTANCE TO MOLTEN METALS AND HOT SOLIDS
9



RESISTANCE TO SURFACE DAMAGE BY FINE PARTICLES
K



ANTI-MIST
N



BSI KITEMARK
Yes

MATERIAL
Polycarbonate



PRODUCT WEIGHT
216g



RECYCLABLE



KIT
Supplied With: EVO 2,3,5,DS,Lite,Skyworker Arms.
EVO8/EVOLite Badgeholder Arms. EVOGuard
Browguard Mounting System



JSP Limited. Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change.

Page 1 of 2 / Issued 2 Jun 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



COMPATIBLE PRODUCTS

EVO®2 Mid Peak with Slip
 EVO®2 Vented with Slip Ratchet
 EVO®3 Micro Peak Slip Ratchet
 EVO®3 Linesman Slip Ratchet
 EVO®3 Micro Peak Slip Ratchet Vented
 EVO®3 Micro Peak Wheel Ratchet
 EVO®3 Micro Peak Wheel Ratchet Linesman
 EVO®3 Micro Peak Wheel Vented
 EVO®3 Mid Peak Slip Ratchet
 EVO®3 Mid Peak Slip Ratchet Vented
 EVO®3 Mid Peak Wheel Ratchet
 EVO®3 Mid Peak Wheel Ratchet Vented
 EVO®3 OneTouch™ Slip Ratchet

 EVO®3 OneTouch™ Slip Ratchet Vented
 EVO®3 Revolution® Wheel Ratchet Vented
 EVO®5 Dualswitch™ Micro Peak Wheel Ratchet Vented
 EVO®5 Olympus® Mid Peak Slip Ratchet Vented
 EVO®5 Olympus® Mid Peak Wheel Ratchet
 EVO®5 Olympus® Mid Peak Wheel Ratchet Vented
 EVO®5 Olympus® Mid Peak Wheel Ratchet Vented Linesman
 EVO®8 Wheel Ratchet
 EVO®8 Wheel Ratchet Linesman
 EVO®8 Wheel Ratchet Vented
 EVOLite® Micro Peak Slip Ratchet
 EVOLite® Linesman Slip Ratchet
 EVOLite® Micro Peak Slip Ratchet Vented
 EVOLite® Micro Peak Wheel Ratchet
 EVOLite® Micro Peak Wheel Ratchet Linesman
 EVOLite® Micro Peak Wheel Ratchet Vented
 EVOLite® Micro Peak Wheel Ratchet Vented Linesman
 EVOLite® Mid Peak Slip Ratchet
 EVOLite® Slip Ratchet Vented
 EVOLite® Mid Peak Wheel Ratchet
 EVOLite® Mid Peak Wheel Ratchet Vented
 EVOLite® Skyworker™
 Sonis® Compact Helmet Mounted Ear Defenders
 Sonis®1 Helmet Mounted Ear Defenders
 Sonis®3 Helmet Mounted Ear Defenders

APPLICATIONS

Agricultural
 • Arborist
 • Chemical Spraying
 • Farming
 • Grain Stores
 • Landscaping
 • Aircraft Maintenance
 • Ground Maintenance

 Construction and Infrastructure

 Facilities Management

 Food and Drink Manufacturing
 • Automotive
 • Cosmetics
 • Foundries and Metals
 • Injections Moulding
 • Paper
 • Pharmaceutical
 • Shipyard and Boat Building

 Mining, Aggregates and Quarrying

 Oil, Gas and Chemical Companies

 Renewable, Wind and Solar Energy
 • Electrical
 • Water and Plumbing

 Utilities Contractors

 • Electrical
 • TM Companies
 • Water

