

Safety Data Sheet according to WHS Regulations

Printing date 13.07.2017 Revision: 13.07.2017

1 Identification

Product Name: REPAIR EXPRESS CEMENT

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Sealant

Details of Manufacturer or Importer:

Soudal Australia Pty Ltd Unit 1, 29 Prince William Drive Seven Hills NSW 2147

Phone Number: 02 8678 7449

Emergency telephone number: 1300 507 011

2 Hazard(s) Identification

Hazardous Nature:

Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

The product is not classified according to the Globally Harmonised System (GHS).

Signal Word Void

Hazard Statements Void

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: No reportable hazardous substances or complex substances.

Hazardous Components: Void

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek medical attention if symptoms occur.

Symptoms Caused by Exposure: No adverse health effects expected.

5 Fire Fighting Measures

Suitable Extinguishing Media: Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 13.07.2017 Revision: 13.07.2017

Product Name: REPAIR EXPRESS CEMENT

(Contd. of page 1)

Specific Hazards Arising from the Chemical:

Hazardous combustion products include including oxides of carbon.

Product is not flammable.

Containers close to fire should be removed if safe to do so.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and scoop up solid spill and place into a suitable container for disposal. Clean spill area with an excess of water.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use.

Store at room temperature.

Max. storage time: 1 year.

Suitable packaging material: Synthetic material.

8 Exposure Controls and Personal Protection

Exposure Standards:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Respiratory protection is not required under normal use conditions.

Use an approved vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Impervious gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 13.07.2017 Revision: 13.07.2017

Product Name: REPAIR EXPRESS CEMENT

(Contd. of page 2)

frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eve and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form: Paste

Colour: Variable in colour, depending on the composition.

Odour: Characteristic

Odour Threshold: No information available pH-Value: No information available No information available Melting point/freezing point: **Initial Boiling Point/Boiling Range:** No information available Flash Point: No information available Product is not flammable. Flammability: Auto-ignition Temperature: No information available **Decomposition Temperature:** No information available

Explosion Limits:

No information available Lower: Upper: No information available Vapour Pressure: No information available

Relative Density: 1.67

Vapour Density: Not applicable

Evaporation Rate: No information available

Solubility in Water: Soluble

Partition Coefficient (n-octanol/water): No information available

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: No further relevant information available. Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: Oxides of carbon.

11 Toxicological Information

Toxicity:

LD₅₀/LC₅₀ Values Relevant for Classification: No information available

Acute Health Effects

Inhalation: No adverse health effects expected. Skin: No adverse health effects expected. Eye: No adverse health effects expected. Ingestion: No adverse health effects expected.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met.

Respiratory or Skin Sensitisation: Based on classification principles, the classification criteria are not met.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 13.07.2017 Revision: 13.07.2017

Product Name: REPAIR EXPRESS CEMENT

(Contd. of page 3)

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

Chronic Health Effects: No information available

Existing Conditions Aggravated by Exposure: No information available

Additional toxicological information: No information available

12 Ecological Information

Ecotoxicity: No adverse ecological effects are expected. **Aquatic toxicity:** No further relevant information available.

Persistence and Degradability: Contains non readily biodegradable component(s).

Bioaccumulative Potential: No further relevant information available.

Mobility in Soil: No further relevant information available.

Other adverse effects:

Not classified as dangerous for the ozone layer.

None of the known components is included in the list of fluorinated greenhouse gases

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number Not regulatedProper Shipping Name Not regulatedDangerous Goods Class Not regulatedPacking Group: Not regulated

15 Regulatory Information

Australian Inventory of Chemical Substances: This product contains no hazardous ingredients.

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:

Not Scheduled.

16 Other Information

Date of Preparation or Last Revision: 13.07.2017

Prepared by: MSDS.COM.AU Pty Ltd www.msds.com.au

(Contd. on page 5)

Safety Data Sheet according to WHS Regulations

Printing date 13.07.2017 Revision: 13.07.2017

Product Name: REPAIR EXPRESS CEMENT

(Contd. of page 4)

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Soudal Australia Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.