

## tesa® 53314

### Non-staining high strength mono filament tape

tesa® 53314 is a high strength polyester backed fiberglass reinforced filament tape.

tesa® 53314 has a high tack and high shear resistant adhesive system. It has excellent aging properties and assures clean removal from most substrates. Furthermore it is non-staining.

### Main Application

- Transport securing of commercial and home appliances
- Securing and reinforcement of furniture for moving
- Bundling and reinforcement of glass-windows for transportation
- Splicing of metal sheets during fabrication and processing
- Fixation of metal coil ends for safe and reliable transportation

### Technical Data

▪ Backing material	glassfibre / PET film	▪ Adhesion to steel	5 N/cm
▪ Total thickness	220 µm	▪ Elongation at break	5 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	680 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=53314>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.