



Use MOTIP Quick Start for eliminating internal combustion engine starting problems of both petrol and diesel engines. The spray is ether-based.

Ord.-no: 090405, 290405

Quality & properties

Fast-acting
Ether-based
Misty spray pattern

Physical & chemical data

Base: Diethylether with mineral oil
Colourname: no colour
Smell: Characteristic
Surfaces: Diesel engines, Petrol engines
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 years
Content:

- 500 ML
- 200 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The aerosol should have room temperature.
Before use, shake the aerosol.
Inject quick start into the air inlet of the air filter for several seconds.
Start the engine.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.