

MOTIP Marking Spray

Technical Information



Fast-drying marking spray to mark stone, concrete, asphalt and metal. Marking spray has very high coverage, is wear-resistant and resistant to petrol, chemicals and the weather.

Ord.-no: 000028, 000029, 000030, 000031

Quality & properties

- Very high coverage
- Wear resistant
- Resistant to petrol, chemicals and weather influences
- Fast drying

Physical & chemical data

Base: Acrylic resin
Colourname:

- blue
- red
- white
- yellow

Smell: Neutral
Efficiency: 600 ML – 40 m²
Dry to touch: 30 - 60 min
Completely dry: 24 h
Surfaces: Stone, concrete, asphalt and metal.
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Content: 600 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The surface must be clean, dry and free of grease.
The aerosol should have room temperature. Best processing temperature 10 to 25°C.
Before use, shake the aerosol for 2 minutes and spray a sample.
Apply the marking spray in the desired width.
After use, clean the valve (hold the can upright and press the nozzle for approximately 5 seconds).
The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.