

STEP'MAT EVOL

P70SI6K

Low-cut safety shoe S3S F0 CI HI SR



Benefits

- Abrasion-resistant reinforcement at the toe and heel for enhanced protection
- Non-magnetic, antistatic
- No metal parts
- Reflective inserts on the sides for improved visibility

Uses

- Building and civil engineering
- Outdoor work
- Dry environments
- Wet environments

Packaging

- 40 to 45: boxes of 10 pairs
- 37 to 39 and 46 to 48: boxes of 5 pairs
- Sales unit: pair

Size	Code
37	71 923 223
38	71 923 231
39	71 923 258
40	71 923 266
41	71 923 274
42	71 923 282

Size	Code
43	71 923 290
44	71 923 304
45	71 923 312
46	71 923 320
47	71 923 339
48	71 923 347

Description

- Low-top safety shoe
- Water-repellent full grain leather upper with a brown pull-up finish
Thickness 2.0 mm
- Abrasion-resistant reinforcement at the toe and heel for enhanced protection and extended life
- Reflective inserts on the sides
- STRESS OUT SYSTEM bellows tongue, quilted on the instep for optimal comfort, combined with two lateral gussets to prevent solid particles entering the shoe
- Padded collar for flexibility and comfort
- WING TEX breathable mesh lining for improved foot ventilation
- Lace-up fastening through 4 pairs of non-metallic eyelets
- AIR TOE composite toe cap
- SAVE & FLEX PLUS “zero-millimetre” metal-free puncture-resistant midsole - lightweight, flexible, non-magnetic and athermal
- 100% protection of the sole of the foot
- Puncture resistance > 1100 Newtons
- POLYSOFT removable, anatomical, sweat-reducing insole. Preformed to the shape of the foot on an injected PU support
- Bi-density, anti-torsion, anti-abrasion and antistatic PU outsole
- Resistant to oils and hydrocarbons
- Slip resistance rating (SR) in compliance with standard EN ISO 20345
- The combination of AIR TOE, WING TEX and POLYSOFT technologies provides enhanced comfort and keeps the feet cool and dry
- Weight (size 42): 640 g

Standards

- EN ISO 20345 : 2022 S3S F0 CI HI SR

